

## **WERIT - Packaging Specification**

**Short description:** IBC 600 I UN in standard design with plastic pallet

**Technical data:**

**Measures (mm):** Length: 1.200,0 +/- 5,0  
Width: 800,0 +/- 5,0  
Height: 1.010,0 +/- 5,0

**Weight (kg):** approx. 46,200

**Capacity (l):** 600,0

**Overflow capacity (l):** 645,0

**Material / Technical Requirements / Processing:**

Inner Bottle:	- PE-HD, natural, UV-stabilized - weight (kg): approx. 12,5
Filling opening / Screw cap:	- opening 150,0 mm - sealable screw cap, black, NW150 with S160x7 internal thread - sealing ring: foam rubber, 445 x 7 mm
Discharge/Discharge closure:	- opening 50,0 mm - integrated valve, natural, NW50 with S60x6 outer thread, - sealing ring: PCP, 38 x 7 mm - handle PE-HD, blue - sealing for the handle: Viton, 18 x 3 mm - aluminium sealing welded on the front of the valve - sealable screw cap, black, NW50, with S60x6 internal thread
Cage:	- steel cage made of steel tubes of 18x1mm (horizontal) and 30x1mm (vertical), galvanized inside and outside - cross jointer made of a steel tube, galvanized inside and outside - weight (kg): approx. 18,6
Marking:	- labelling plate 722x350mm, galvanized on both sides - weight (kg): approx. 1,1
Pallet:	- 4-way entry runner plastic pallet, 1200x800mm - weight (kg): 13,5
Accessories:	- outlet pipe bend, natural, NW50 with S60x6 internal and outer thread - corner protectors, black, 4 pieces